



FLECK® 3900



FEATURES/BENEFITS

Lead-free brass valve body for superior strength and durability
Continuous service flow rate of 250 GPM with a backwash of 100 GPM
Backwash capability accommodates softener tanks up to 63" and filter up to 42" in diameter
Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system
Designed for single or multiple tank systems

Environmental protective cover for water resistance, corrosion resistance, and UV stability
Time-tested, hydraulically-balanced piston for service and regeneration
Rugged-built electromechanical timer designed with heavy duty 3/8" wide plastic gears

OPTIONS

Filter or softener control valves
Downflow co-current or upflow counter-current regeneration
No hard water bypass piston
Brine cam auxiliary switch
Electromechanical timer auxiliary switch
Treated water regeneration

VALVE SPECIFICATIONS

Valve Material	Lead-free brass*
Inlet/Outlet	3" NPTF/BSPF
Cycles	3 or 5

FLOW RATES (50 PSI INLET) – VALVE ALONE

Continuous	250 GPM (56.8 m
------------	-----------------



FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

40742 REV D JL14 © 2013 Pentair Residential Filtration, LLC. All Rights Reserved.